

# FEL-PRO

Pure Federal-Mogul Performance®

FEL-PRO

## FORD, MERCURY V8 260, 289, 302 EXCEPT "BOSS"; 351 ENG., 1962-93

Set Type/ No.	Application	Dimensions	Materials Construction
INTAKE <b>1250</b>	All stock and small race port heads	Thickness: .060 (1/16") Port Size: 1.20" x 2.00"	Standard w/Printoseal
<b>1262</b>	Large race Also: Fits TFS, GT-40, and "N" heads	Thickness: .060 (1/16") Port size 1.28" x 2.10"	Standard w/Printoseal
EXHAUST <b>1415</b>	1962-93	Port Size-. 1.25" x 1.48"	Perforated steel core w/antistick coating
<b>1486</b>	J302 & K302 (Dual bolt pattern, stock Ford and splayed AR)	Port Size: 1.40" x 1.40"	Perforated steel core w/antistick coating
<b>1487</b>	Dart & TFS, E351 (Dual bolt pattern, stock Ford and inline spread bolt Dart & TFS)	Port Size: 1.42" x 1.62"	Perforated steel core w/antistick coating
VALVE COVER <b>1613</b>	1962-87	Thickness: 3/16"	Blue Stripe cork-rubber
<b>1614</b>	1962-87	Thickness: 5/32"	Fel-CoPrene rubber
<b>1645</b>	1962-87	Thickness: 5/16"	Cork-Lam cork-rubber w/steel core
OIL PAN			
<b>1809</b>	1962-92 Except 351W eng.	Thickness-. 3/32"	Rubber coated fiber
<b>1810</b>	351W eng.	Thickness: 3/32"	Rubber coated fiber
<b>1827</b>	351W eng. Notch for main cap and trimmed for strokers.	Thickness: 3/32"	Rubber coated fiber w/steel core
REAR MAIN BRG. SEAL <b>2901</b>	260. 289. 302 eng., 1962 -11/30-82		Premium material, 2 piece
<b>2922RS</b>	302 eng., 11/30/82-93		Premium material, 1 piece
<b>2902</b>	351 W 1969-7/10/88		Premium material, 2 piece
<b>2921</b>	7/10/83-93		Premium material, 1 piece
R.A.C.E. SET <b>2718</b>	302 eng., 12/1/82-1993		Does not contain full circle rear main bearing seal
<b>2707-1</b>	260, 289, 302 eng., 1962 - 11/30/82		Does not contain full circle rear main bearing seal
<b>2709-1</b>	351 W eng., 1969 - 7/10/83		Does not contain full circle rear main bearing seal

SHIP • RELIABLE PARTS • DEPENDABLE SERVICE • QUALITY CRAFTSMANSHIP • RELIABLE PARTS • DEPENDABLE SERVICE

LEXINGTON MOORESVILLE  
**1(800)222-6805 • 1(800)615-6759**  
**FAX: 1(336)249-4922 • www.centralhp.com**



129

