

## General Information and Data HIGH PERFORMANCE OIL FILTER LINE PERFORMANCE AND FEATURES

MODEL	SAFETY VALVE OPENING PRESSURE	SAFETY VALVE SCREEN	NOMINAL MICRON RATING	RECOMMENDED MAXIMUM FLOW(GPM)	RECOMMENDED MAXIMUM OPERATING PRESSURE(PSI)	MINIMUM BURST PRESSURE (PSI)	ANTI-DRAIN VALVE	CENTER TUBE TYPE	THREAD SIZE	GASKET LOCATION
<b>3 5/8" Tall (5.73") Filters</b>										
HP1	22 psi	Yes	18 micron	10	200	500	Yes	Spiral	3/4-16 UNF-2B	Inboard
HP2	22 psi	Yes	18 micron	10	200	500	Yes	Spiral	13/16 - 16 UN-2B Sp	Inboard
HP4	22 psi	Yes	18 micron	10	200	325	Yes	Spiral	13/16 - 16 UN-2B Sp	Outboard
<b>3 5/8" Short (4.01") Filters</b>										
HP3	22 psi	Yes	18 micron	10	200	500	Yes	Spiral	3/4-16 UNF-2B	Inboard
HP5	22 psi	Yes	18 micron	10	200	500	Yes	Spiral	13/16 - 16 UN-2B Sp	Inboard
HP8	22 psi	Yes	18 micron	10	200	325	Yes	Spiral	13/16 - 16 UN-2B Sp	Outboard
<b>3 5/8" Extra Tall (8.72") Filter</b>										
HP12	22 psi	Yes	18 micron	10	200	325	Yes	Spiral	13/16-16 N-2B Sp	Outboard
<b>3" Short (3.30") Filters</b>										
HP7	22 psi	Yes	18 micron	6	200	325	Yes	Spiral	3/4-16 UNF-2B	Outboard
HP9	22 psi	Yes	18 micron	6	200	325	Yes	Spiral	M18 x 1.5 6H	Outboard
<b>3" Tall (4.89") Filters</b>										
HP10	22 psi	Yes	18 micron	8	200	325	Yes	Spiral	3/4-16 UNF-2B	Outboard
HP11	22 psi	Yes	18 micron	8	200	325	Yes	Spiral	M18 x 1.5 6H	Outboard
<b>4 1/2" (6.12") Filters</b>										
HP6	22 psi	No	12 micron	20	200	400	No	Spiral	1 1/2 - 12 UNF-2B	Outboard
HP6A	22psi	Yes	12 micron	20	200	400	No	Spiral	1 1/2 - 12 UNF-2B	Outboard

FRAM

SHIP • RELIABLE PARTS • DEPENDABLE SERVICE • QUALITY CRAFTSMANSHIP • RELIABLE PARTS • DEPENDABLE SERVICE

LEXINGTON MOORESVILLE  
**1(800)222-6805 • 1(800)615-6759**  
**FAX: 1(336)249-4922 • www.centralhp.com**

