



Ultra Lite 2 5/8" Mechanical Gauges

Ultra-Lite gauges are the hottest instruments in motorsports. Aluminum construction greatly reduces weight while satin anodized aluminum dials and bright red fluorescent pointers make them easy to read. A quality engineered mechanism provides proven durability and accuracy with a 270° sweep.



4421

- 4401 Boost 30 In. HG/20 PSI
- 4402 Blower Press 0-60 PSI
- 4403 Boost 30 In. HG/30 PSI

Above includes 6 ft. nylon tubing 1/8" & 1/4" NPT fittings.

- 4407 Water Press 0-35 PSI
- 4411 Fuel Press 0-15 PSI
- 4412 Fuel Press 0-100 PSI

Both 4411 & 4412 require braided stainless steel line & mounting cups. Must be mounted outside of vehicle unless isolator is used.

- 4413 Fuel Press With Isolator 0-15 PSI

May be installed inside vehicle by mounting isolator in engine compartment. See information with photo below.

- 4421 Oil Pressure 0-100 PSI
- 4422 Oil Pressure 0-200 PSI

The above Pressure gauges include 1/8" & 1/4" NPT fitting along with 6 ft. nylon tubing.

- 4424 Pressure 0-400 PSI
- 4425 Pressure 0-600 PSI

The above Pressure gauges require braided stainless steel line.

- 4426 Brake Pressure 0-2,000 PSI

Includes T-fitting and 3/8" OD x 1/8"-27 NPT fitting. Use only approved brake line (not included).

- 4428 Nitrous Pressure 0-1,600 PSI

Includes 1/8" NPT x -4 fitting, special restrictor fitting. Requires braided stainless steel line for installation.

- 4431 Water Temperature 140°-280° F (6 FT. TUBING)
- 4432 Water Temperature 120°-240° F (6 FT. TUBING)
- 4433 Water Temperature 120°-240° F (12 FT. TUBING)
- 4434 Water Temperature 140°-280° F (3 FT. TUBING)
- 4435 Temperature 140°-340° F (8 FT. TUBING)
- 4436 Temperature 140°-340° F (4 FT. TUBING)
- 4441 Oil Temperature 140°-280° F (6 FT. TUBING)
- 4451 Trans Temperature 140°-280° F (8 FT. TUBING)

The above Temperature gauges include 1/2" NPT fittings and capillary tubing (length noted in description).

- 4471 Vacuum 30 IN. HG.

Includes 6 ft. tubing, 1/8" NPT & universal T-fitting.



4424

4425

4428



4401

4402

4411

4412



4421

4422

4426

4431, 4434



4432

4441

4451

4471



4313

Isolator allows gauge to be mounted in vehicle's interior without danger of fuel entering the driving compartment.

Includes, 4ft. braided stainless steel line connecting isolator to gauge. Requires braided stainless steel line to connect isolator to fuel source.



Temperature Adapters

- 2263 3/8" Brass NPT adapter Fitting
- 2264 1/2" Brass NPT adapter fitting



Extension Adapters

- 2270 1/2" NPT Temp. Extension
- 2271 3/8" NPT Temp. Extension

BLE SERVICE • QUALITY CRAFTSMANSHIP • RELIABLE PARTS • DEPENDABLE SERVICE • QUALITY CRAFTSMAN

