

STREET PERFORMANCE SEALS

(No Machining Required)

Crane Cams offers these valve stem seals for use with our stock diameter valve springs. These finest quality seals offer correct oil control and durability and can be installed without having to machine the cylinder head, saving you time and money for street performance applications.



PERFORMANCE SEALS

APPLICATION	VALVE STEM DIA.	TYPE	SEAL O.D.	SET OF 16 PART NO.
Chevrolet V-8 262 thru 400	11/32"	Umbrella	.675	99819-16

HI-PERFORMANCE TEFLON SEALS

(Machining Required)

Crane Teflon® valve stem seals provide maximum valve stem oil control. These seals wipe excess oil from the valve stem by means of a unique spring loaded wiper assembly, thus preventing unwanted oil from reaching and contaminating the cylinder. Machining usually required.



TEFLON SEALS

VALVE STEM DIA.	MACHINING TOOL GUIDE O.D.	SEAL O.D.	PART NO.	MACHINING TOOL	ARBOR
5/16"	.531	.620	99824-16	99016-1	Included with Tool
11/32"	.500	.600	99826-16	99037-1	99027-1
11/32"	.531	.620	99820-16	99017-1	Included with Tool
3/8"	.500	.600	99828-16	99037-1	99028-1
3/8"	.531	.620	99822-16	99018-1	Included with Tool

ALSO AVAILABLE IN BULK.

MACHINED STEEL LOCKS 10°

SINGLE GROOVE DESIGN

Many engine builders prefer a 10° taper and these machined steel locks are perfect for any racing application where the 10° design is specified. (Use only with 99630, 99631, 99632 or 99633 retainers).

For 11/32" dia.
Valve Stems
99081-1

For 3/8" dia.
Valve Stems
99082-1



99081-1

SHIP • RELIABLE PARTS • DEPENDABLE SERVICE • QUALITY CRAFTSMANSHIP • RELIABLE PARTS • DEPENDABLE SERVICE

LEXINGTON MOORESVILLE
1(800)222-6805 • 1(800)615-6759
FAX: 1(336)249-4922 • www.centralhp.com

